

# HD30L



Hotel/hospitality  
features



Customisable  
faceplate



Anti-bacterial  
housing



Power over Ethernet  
(PoE)



HD audio

## Stylish, corded SIP lobby phone

Thanks to the "automatic dialing when picking up the handset" feature, you can't dial the wrong number. The Snom lobby phone ensures flawless usability. The connection to a predetermined destination, e.g.

the switchboard, is made immediately after you pick up the handset. The HD30L can be customized thanks to a faceplate on the telephone base.

## Basics and equipment

- Product information
  - Lobby phone | Corded handset | PN 00007019
  - Colour: gunmetal black
- Equipment
  - Anti-bacterial housing
  - Sturdy, solid construction
  - [Fully customisable faceplate for hotel branding and dialing instructions<sup>1</sup>](#)
- Placement: indoor, desktop, nightstand, wall mounting

## Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Corded handset (on the base cradle, desk mounted): 182 mm × 53 mm × 146 mm
  - Corded handset (on the base cradle, wall mounted): 216 mm × 53 mm × 56 mm
- Weight (approx.)
  - Corded handset (on the base cradle): 400 g

## Indicators and keys

- Corded handset: 2 LED indicators
  - Mute status indication: 1 red LED
  - Speakerphone mode: 1 red LED
- Corded handset: 4 dedicated audio keys
  - Mute (with red LED)
  - Speakerphone mode (with red LED)
  - *VOL+* → Volume +
  - *VOL-* → Volume -

## Audio devices and features

- Corded handset
  - Microphone
  - Handset earpiece
  - External speaker
- Hearing aid compatible (HAC)
- Built-in assignable ringtones

## Interfaces and connections

- Power options
  - [Power over Ethernet \(PoE\)](#)
    - IEEE 802.3af, class 2
- Wired interfaces
  - Telephone base
    - Network connectivity: RJ45-8P8C socket → Gigabit Ethernet (GbE)
    - Handset cord: custom socket
  - Corded handset
    - Handset cord: custom socket

## Administration interfaces and setup

- Configuration and setup via voice menu
- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
- Advanced SIP configuration tool for easy mass deployment and phone monitoring
- [Secure Redirection And Provisioning Service \(SRAPS\)](#) support

## Interoperability

- Interoperable with all major IP-PBX platforms

## Networking technologies and protocols

- VLAN support
- SIP (RFC 3261)

## Call features

- 1 SIP identity / account
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Multicast paging

## Environmental conditions

- Operating ambient temperature:
  - 5 °C - +45 °C
- Humidity (non-condensing)
  - 5 % - 95 %

## Package contents

- Hardware
  - Telephone base
  - Handset
  - Handset cord: 330 mm
  - Footstand
  - Wall mount kit
  - 2 Ethernet cables: Cable length (approx.) 125 mm | 2 m
- Documentation
  - [Quick Installation Guide](#)

## Snom accessories and compatible devices

- PoE injector: [A5 \(PN 00004065\)](#)

## Series overview



<sup>1</sup> Available separately

<sup>2</sup> Also available as analogue model

## Disclaimer

Further information: [Snom HD30L webpage](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.